



## Specifically Designed for Enclosed Cargo Trailers

### TRED-eXtreme Performance

#### Construction

- TRED-eXtreme® is a performance engineered floor and ramp panel with a high-density polyethylene (HDPE) overlay laminated on one or both sides.
- TRED-eXtreme can be specified with two different panel substrates—western plywood or PAKtite® Cargo Panels.
- The panel substrate can be specified in a variety of sizes and thicknesses.
- The HDPE overlay can be specified in a variety of thicknesses, textures and colors.

### TRED-eXtreme Specifications

#### Features

- TRED-eXtreme is dimensionally stable with superior strength and stiffness.
- The HDPE surface is a 100% moisture barrier that is resistant to fuel, solvents and most chemicals.
- The HDPE textured surface is slip resistant and provides tremendous abrasion resistance.
- HDPE surface scratches and gouges are visually minimized because the color is pigmented throughout the entire laminate.
- TRED-eXtreme panel edges are finished with an emulsified wax/acrylic edge seal to minimize moisture absorption.



#### Packaging

TRED-eXtreme is unitized with three plastic straps and corner protectors banded to 1-1/2" runners.

| Thickness | Size    | Weight           | Pcs/Unit |
|-----------|---------|------------------|----------|
| 5/8"      | 48"x96" | 1.83 lbs./sq.ft. | 50       |
| 3/4"      | 48"x96" | 2.34 lbs./sq.ft. | 40       |

*Special thicknesses and sizes available on request.*

#### Handling

Store TRED-eXtreme indoors on a flat surface, or covered and above ground away from standing water.

For best performance, acclimatize TRED-eXtreme to local equilibrium moisture content before installing.

Once installed, TRED-eXtreme requires very little maintenance and can be easily cleaned.

#### Warranty

TRED-eXtreme will perform as a structural floor and ramp when properly installed by an approved enclosed cargo trailer manufacturer in accordance with accepted industry practices.

TRED-eXtreme is warranted to be free of manufacturing defects, including glue line failure, for two years. Affiliated Resources, Inc. has the right to inspect and will, at its option, replace or make reasonable allowance for defective TRED-eXtreme panels. The TRED-eXtreme Warranty does not cover fading or discoloration.

Affiliated Resources, Inc. will not be held liable for any incidental or consequential damages, nor any damages that are the result of the misuse or improper installation of TRED-eXtreme.



Member Company



**AFFILIATED RESOURCES**  
PROVIDING SOLUTIONS