

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.21.2020

Page 1 of 15

**Dyna Span®, Dyna Slide®, Dyna Shield®**

### SECTION 1: Identification

#### Product identifier

**Product name:** Dyna Span®, Dyna Slide®, Dyna Shield®

**Additional information:** Note: Wood products are not hazardous under the criteria of the OSHA Hazard Communication Standard 29 CFR 1910.1200. However, these products may become hazardous as the result of downstream activities (e.g. cutting, sawing, sanding and machining) which create small dust particles resulting in the hazard classifications described below.

#### Recommended use of the product and restriction on use

**Relevant identified uses:** Building Material - Industrial, Construction, Component Parts.

**Uses advised against:** Any use other than that recommended above.

**Reasons why uses advised against:** Not determined or not applicable.

#### Manufacturer or supplier details

**Manufacturer:**

**United States**

Affiliated Resources  
5 Centerpointe Drive  
Suite 530  
Lake Oswego, OR 97035  
(503) 228-3802

#### Emergency telephone number:

**United States**

Affiliated Resources  
(503) 228-3802 (24 hours)

### SECTION 2: Hazard(s) identification

#### GHS classification:

Skin irritation, category 2  
Eye irritation, category 2A  
Skin sensitization, category 1  
Respiratory sensitization, category 1  
Carcinogenicity, category 1A  
Specific target organ toxicity - single exposure, category 3, respiratory tract irritation  
Specific target organ toxicity - repeated exposure, category 2  
Combustible Dust

#### Label elements

**Hazard pictograms:**

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.21.2020

Page 2 of 15

Dyna Span®, Dyna Slide®, Dyna Shield®



**Signal word:** Danger

## Hazard statements:

Combustible Dust May form combustible dust concentrations in air.  
H315 Causes skin irritation  
H319 Causes serious eye irritation  
H317 May cause an allergic skin reaction  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled  
H350 May cause cancer via inhalation.  
H335 May cause respiratory irritation  
H373 May cause damage to organs through prolonged or repeated exposure

## Precautionary statements:

P201 Obtain special instructions before use  
P202 Do not handle until all safety precautions have been read and understood  
P264 Wash skin thoroughly after handling  
P271 Use only outdoors or in a well-ventilated area  
P272 Contaminated work clothing must not be allowed out of the workplace  
P280 Wear protective gloves/protective clothing/eye protection/face protection  
P260 Do not breathe dust/fume/gas/mist/vapors/spray  
P302+P352 IF ON SKIN: Wash with plenty of water  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention  
P321 Specific treatment (see first aid instructions on this label)  
P362 Take off contaminated clothing and wash it before reuse  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P337+P313 If eye irritation persists: Get medical advice/attention  
P363 Wash contaminated clothing before reuse  
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor  
P308+P313 IF exposed or concerned: Get medical advice/attention  
P405 Store locked up  
P403+P233 Store in a well-ventilated place. Keep container tightly closed  
P501 Dispose of contents/container according with all local, regional, state and federal regulations.

**Hazards not otherwise classified:** None

## SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: N/A	Wood/Wood Dust	80-95
CAS number: 9003-35-4	*Cured Phenol-Formaldehyde Resin Solids	<10
CAS number: 9016-87-9	*Cured Polymeric Diphenylmethane Diisocyanate (PMDI) Adhesive	<10

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.21.2020

Page 3 of 15

**Dyna Span®, Dyna Slide®, Dyna Shield®**

CAS number: N/A	Polyurea/Polyurethane Solids	<6
CAS number: 68514-74-9	Palm Wax	<2
CAS number: 8030-12-4	Tallow Wax	<2
CAS number: N/A	Release Agent	<1
CAS number: N/A	Edge Sealant	<1

## Additional Information:

The specific chemical identity and/or exact percentages (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200)

\* Some panel products are produced solely with PMDI resins, solely with PF resins or with a mixture of the two depending on manufacturing location and specific product recipes.

## SECTION 4: First aid measures

### Description of first aid measures

#### General notes:

Show this Safety Data Sheet to the doctor in attendance.

#### After inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention.

#### After skin contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

#### After eye contact:

Rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

#### After swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

### Most important symptoms and effects, both acute and delayed

#### Acute symptoms and effects:

Eye contact may result in irritation, redness, pain, inflammation, itching, burning and tearing.

Dermal exposure may cause an allergic skin reaction. Symptoms may include irritation, redness, pain, rash, inflammation, itching, burning and dermatitis.

Product presents an explosion hazard when suspended in air under certain conditions. Inhalation of large amounts of dust may cause inflammation and irritation of the nose and throat. Symptoms may include cough, sore throat, tightness of the chest, chest pain and lightheadedness.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.21.2020

Page 4 of 15

**Dyna Span®, Dyna Slide®, Dyna Shield®**

## Delayed symptoms and effects:

Exposure may cause cancer. Effects are dependent on exposure (dose, concentration, contact time).  
May cause damage to organs through prolonged or repeated exposure. Effects are dependent on exposure (dose, concentration, contact time).

## Immediate medical attention and special treatment

### Specific treatment:

If respiratory symptoms persist, seek medical attention.

### Notes for the doctor:

Treat symptomatically.

## SECTION 5: Firefighting measures

### Extinguishing media

#### Suitable extinguishing media:

Use water spray, dry chemical or carbon dioxide when fighting fires involving this material. Dry sand or earth can be used for small fires.

#### Unsuitable extinguishing media:

Do not use halogenated extinguishing agents and alcohol-based foam.

### Specific hazards during fire-fighting:

May form combustible dust concentrations in air. Reacts with water and alcohols. Reacts violently with oxidants, strong acids and bases and chlorinated hydrocarbons. This generates a fire and explosion hazard. Thermal decomposition may produce irritating/toxic fumes/gases.

### Special protective equipment for firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode. Use shielding to protect against bursting containers.

### Special precautions:

Violent reactions may result from the use of a water jet or halogenated extinguishing agents. When using extinguishers, avoid dispersing combustible dust into the air. Aim extinguishers directly at the base of the flames and apply the agent as gently as possible. Overall, give preference to using medium to wide spray patterns rather than solid streams. Use only non-sparking tools. Fire fight from a protected location or maximum possible distance. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

## SECTION 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures:

Evacuate unnecessary personnel. Extinguish any sources of ignition. Do not ventilate area as this may spread dust. Wear recommended personal protective equipment including suitable respiratory protection (see Section 8). Ensure no sources of electric discharge or ignition are on your person before entering area. Do not get on skin, eyes or on clothing. Avoid breathing dust, fumes. Wash thoroughly after handling. Remove contaminated clothing and launder before reuse.

### Environmental precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

### Methods and material for containment and cleaning up:

Avoid dust generation or stirring up of dust. Use only non-sparking tools. Ground all equipment used for recovery and clean up. Vacuum up and place in suitable containers for future disposal. Only use vacuum

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.21.2020

Page 5 of 15

**Dyna Span®, Dyna Slide®, Dyna Shield®**

cleaners approved for dust collection. Dispose of in accordance with all applicable regulations (see Section 13).

## Reference to other sections:

For personal protective equipment see Section 8. For disposal see Section 13.

## SECTION 7: Handling and storage

### Precautions for safe handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Use dust explosion proof electrical equipment and lighting. Avoid dust generation and dispersal of dust in air. Dust deposits should not be allowed to accumulate on surfaces. Clean dust residues at regular intervals. Do not use brooms or compressed air hoses to clean surfaces. Only use vacuums approved for dust collection. Use only non-sparking tools. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions such as electrical grounding and bonding or inner atmospheres. Keep containers tightly closed and grounded when not in use. Workers whose clothing may have been contaminated should change into non-contaminated clothing before leaving the work premises. Contaminated clothing should be segregated in such a manner so that there is no direct personal contact by personnel who handle, dispose or clean the clothing. Contaminated clothing should not be allowed out of the workplace. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10).

### Conditions for safe storage, including any incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Outside or detached storage is preferred. Inside storage should be in a standard flammable storage cabinet. Store away from incompatible materials (See Section 10).

## SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

### Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
OSHA	Wood/Wood Dust	N/A	8-Hour TWA-PEL: 15 mg/m <sup>3</sup> (Total dust)
	Wood/Wood Dust	N/A	8-Hour TWA-PEL: 5 mg/m <sup>3</sup> (Respirable dust)
NIOSH	Wood/Wood Dust	N/A	REL-TWA: 1 mg/m <sup>3</sup> (Up to 10-hour TWA)
ACGIH	Wood/Wood Dust	N/A	TLV-TWA: 1 mg/m <sup>3</sup> (Inhalable fraction [8-hour])
	Wood/Wood Dust	N/A	TLV-TWA: 0.5 mg/m <sup>3</sup> (Western red cedar, inhalable fraction [8-hour])
United States(California)	Wood/Wood Dust	N/A	8-Hour TWA-PEL: 2 mg/m <sup>3</sup> (All soft and hardwoods, except Western red cedar)
	Wood/Wood Dust	N/A	8-Hour TWA-PEL: 0.5 mg/m <sup>3</sup> (Western red cedar)

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.21.2020

Page 6 of 15

**Dyna Span®, Dyna Slide®, Dyna Shield®**

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Wood/Wood Dust	N/A	PEL-STEL: 5 mg/m <sup>3</sup> (All soft and hardwoods, except Western red cedar)
	*Cured Polymeric Diphenylmethane Diisocyanate (PMDI) Adhesive	9016-87-9	REL-TWA: 12 ug/m <sup>3</sup> ([Acute Inhalation])
	*Cured Polymeric Diphenylmethane Diisocyanate (PMDI) Adhesive	9016-87-9	REL-TWA: 0.08 ug/m <sup>3</sup> ([Chronic Inhalation])

## Biological limit values:

No biological exposure limits noted for the ingredient(s).

## Information on monitoring procedures:

Not determined or not applicable.

## Appropriate engineering controls:

This product is a combustible material which may be ignited by friction, heat, sparks or flames. It is recommended that all dust control equipment (such as local exhaust ventilation and material transport systems) involved in handling this product contain explosion relief vents or an explosion suppression system. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area. Keep static electricity under control, which includes the bonding and grounding of equipment. Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

## Personal protection equipment

### Eye and face protection:

Use safety glasses with side shields or goggles. Do not wear contact lenses when handling or processing this product. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

### Skin and body protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

### Respiratory protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

## General hygienic measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Contaminated clothing should be removed and separated for decontamination. Do not allow contaminated work clothing out of the workplace. Perform routine housekeeping.

## SECTION 9: Physical and chemical properties

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.21.2020

Page 7 of 15

**Dyna Span®, Dyna Slide®, Dyna Shield®**

## Information on basic physical and chemical properties

<b>Appearance</b>	Solid wood product
<b>Odor</b>	Typical wood odor
<b>Odor threshold</b>	Not determined or not available.
<b>pH</b>	Not determined or not available.
<b>Melting point/freezing point</b>	Not determined or not available.
<b>Initial boiling point/range</b>	Not determined or not available.
<b>Flash point (closed cup)</b>	Not determined or not available.
<b>Evaporation rate</b>	Not determined or not available.
<b>Flammability (solid, gas)</b>	Not determined or not available.
<b>Upper flammability/explosive limit</b>	Not determined or not available.
<b>Lower flammability/explosive limit</b>	Not determined or not available.
<b>Vapor pressure</b>	Not determined or not available.
<b>Vapor density</b>	Not determined or not available.
<b>Density</b>	Not determined or not available.
<b>Relative density</b>	Not determined or not available.
<b>Solubilities</b>	Insoluble in water
<b>Partition coefficient (n-octanol/water)</b>	Not determined or not available.
<b>Auto/Self-ignition temperature</b>	200° to 260°C (392° to 500°F)
<b>Decomposition temperature</b>	Not determined or not available.
<b>Dynamic viscosity</b>	Not determined or not available.
<b>Kinematic viscosity</b>	Not determined or not available.
<b>Explosive properties</b>	Not determined or not available.
<b>Oxidizing properties</b>	Not determined or not available.

## Other information

### SECTION 10: Stability and reactivity

#### Reactivity:

Not reactive under recommended handling and storage conditions.

#### Chemical stability:

Stable under recommended handling and storage conditions.

#### Possibility of hazardous reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

#### Conditions to avoid:

Extreme heat, open flames, hot surfaces, sparks, static discharge, ignition sources, dust generation and accumulation and incompatible materials.

#### Incompatible materials:

Oxidizing agents, drying oils.

#### Hazardous decomposition products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### Acute toxicity

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.21.2020

Page 8 of 15

**Dyna Span®, Dyna Slide®, Dyna Shield®**

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:**

Name	Route	Result
Wood/Wood Dust	oral	LD50 Rat: 2900 mg/kg
*Cured Phenol-Formaldehyde Resin Solids	oral	LD50 Rat: >5000 mg/kg
	dermal	LD50 Rat: >2000 mg/kg
	inhalation	LC50 Rat: 7.57 mg/L (2h [Vapor])
*Cured Polymeric Diphenylmethane Diisocyanate (PMDI) Adhesive	inhalation	LC50 Rat: 0.49 mg/L (4 Hour [Mist])
	oral	LD50 Rat: >10000 mg/kg
	dermal	LD50 Rabbit: >9400 mg/kg

## Skin corrosion/irritation

**Assessment:**

Causes skin irritation.

**Product data:**

No data available.

**Substance data:**

Name	Result
*Cured Phenol-Formaldehyde Resin Solids	Causes skin irritation.
*Cured Polymeric Diphenylmethane Diisocyanate (PMDI) Adhesive	Causes skin irritation.

## Serious eye damage/irritation

**Assessment:**

Causes serious eye irritation.

**Product data:**

No data available.

**Substance data:**

Name	Result
Wood/Wood Dust	Wood dust causes eye irritation.
*Cured Phenol-Formaldehyde Resin Solids	Causes serious eye irritation.
*Cured Polymeric Diphenylmethane Diisocyanate (PMDI) Adhesive	Causes serious eye irritation.

## Respiratory or skin sensitization

**Assessment:**

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Product data:**

No data available.

**Substance data:**



# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.21.2020

Page 9 of 15

**Dyna Span®, Dyna Slide®, Dyna Shield®**

Name	Result
Wood/Wood Dust	According to the ACGIH, Western red cedar dust causes dermal and respiratory sensitization. Symptoms of dermal sensitization include an allergic skin reaction. While symptoms of respiratory sensitization include allergy, asthma, or breathing difficulties.
*Cured Phenol-Formaldehyde Resin Solids	May cause an allergic skin reaction.
*Cured Polymeric Diphenylmethane Diisocyanate (PMDI) Adhesive	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

## Carcinogenicity

### Assessment:

May cause cancer.

**Product data:** No data available.

### Substance data:

Name	Species	Result
Wood/Wood Dust		Wood dust may cause nasopharyngeal cancer and/or cancer of the nasal cavities and paranasal sinuses by inhalation.

## International Agency for Research on Cancer (IARC):

Name	Classification
Wood/Wood Dust	Group 1
*Cured Phenol-Formaldehyde Resin Solids	Not Applicable
*Cured Polymeric Diphenylmethane Diisocyanate (PMDI) Adhesive	Not Applicable
Palm Wax	Not Applicable

## National Toxicology Program (NTP):

Name	Classification
Wood/Wood Dust	Known to be human carcinogens
*Cured Phenol-Formaldehyde Resin Solids	Not Applicable
*Cured Polymeric Diphenylmethane Diisocyanate (PMDI) Adhesive	Not Applicable
Palm Wax	Not Applicable

**OSHA Carcinogens:** Not applicable

## Germ cell mutagenicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

## Reproductive toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.21.2020

Page 10 of 15

**Dyna Span®, Dyna Slide®, Dyna Shield®**

No data available.

**Substance data:** No data available.

## Specific target organ toxicity (single exposure)

### Assessment:

May cause respiratory irritation.

### Product data:

No data available.

### Substance data:

Name	Result
Wood/Wood Dust	May cause respiratory irritation.
*Cured Polymeric Diphenylmethane Diisocyanate (PMDI) Adhesive	May cause respiratory irritation.

## Specific target organ toxicity (repeated exposure)

### Assessment:

May cause damage to organs through prolonged or repeated exposure.

### Product data:

No data available.

### Substance data:

Name	Result
*Cured Polymeric Diphenylmethane Diisocyanate (PMDI) Adhesive	May cause damage to respiratory system through prolonged or repeated inhalation.

## Aspiration toxicity

**Assessment:** Based on available data, the classification criteria are not met.

### Product data:

No data available.

**Substance data:** No data available.

## Information on likely routes of exposure:

Inhalation, Skin contact, Eye contact.

## Symptoms related to the physical, chemical and toxicological characteristics:

Refer to Section 4 of this SDS.

## Other information:

No data available.

## SECTION 12: Ecological information

### Acute (short-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

### Substance data:

Name	Result
*Cured Phenol-Formaldehyde Resin Solids	EC50 Daphnia pulex: 172 mg/L (48 h)
*Cured Polymeric Diphenylmethane Diisocyanate (PMDI) Adhesive	LC50 Danio rerio: >1000 mg/L (96 h)
	EC50 Scenedesmus subspicatus: >1640 mg/L (72 h)
	EC50 Activated Sludge: >100 mg/L (3 h)

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.21.2020

Page 11 of 15

**Dyna Span®, Dyna Slide®, Dyna Shield®**

## Chronic (long-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

### Substance data:

Name	Result
*Cured Polymeric Diphenylmethane Diisocyanate (PMDI) Adhesive	NOEC Daphnia magna: >10 mg/L (21 d)

## Persistence and degradability

**Product data:** No data available.

### Substance data:

Name	Result
*Cured Phenol-Formaldehyde Resin Solids	Readily biodegradable in nature.
*Cured Polymeric Diphenylmethane Diisocyanate (PMDI) Adhesive	Not biodegradable.

## Bioaccumulative potential

**Product data:** No data available.

### Substance data:

Name	Result
*Cured Phenol-Formaldehyde Resin Solids	Not expected to bioaccumulate (log Kow = 2.1 to 2.34).
*Cured Polymeric Diphenylmethane Diisocyanate (PMDI) Adhesive	Due to the fast hydrolysis, exposure of the environment to the substance is unlikely or very low. The log Kow of MDA, the expected hydrolysis product, is 1.55.

## Mobility in soil

**Product data:** No data available.

### Substance data:

Name	Result
*Cured Phenol-Formaldehyde Resin Solids	The substance has a moderate sorption to soil and sediment (log Koc = 2.804 ± 0.001).

## Results of PBT and vPvB assessment

### Product data:

**PBT assessment:** This product does not contain any substances that are assessed to be a PBT.

**vPvB assessment:** This product does not contain any substances that are assessed to be a vPvB.

### Substance data:

#### PBT assessment:

*Cured Phenol-Formaldehyde Resin Solids	The substance is not PBT.
*Cured Polymeric Diphenylmethane Diisocyanate (PMDI) Adhesive	Substance is not PBT.

#### vPvB assessment:

*Cured Phenol-Formaldehyde Resin Solids	The substance is not vPvB.
---	----------------------------

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.21.2020

Page 12 of 15

**Dyna Span®, Dyna Slide®, Dyna Shield®**

\*Cured Polymeric  
Diphenylmethane  
Diisocyanate (PMDI) Adhesive

Substance is not vPvB.

**Other adverse effects:** No data available.

## SECTION 13: Disposal considerations

### Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities. Wood and wood dust are not considered hazardous waste under the Federal Hazardous Waste Regulations in 40 CFR 261.

### Contaminated packages:

Not determined or not applicable.

## SECTION 14: Transport information

### United States Transportation of dangerous goods (49 CFR DOT)

<b>UN number</b>	Not regulated
<b>UN proper shipping name</b>	Not regulated
<b>UN transport hazard class(es)</b>	None
<b>Packing group</b>	None
<b>Environmental hazards</b>	None
<b>Special precautions for user</b>	None

### International Maritime Dangerous Goods (IMDG)

<b>UN number</b>	Not regulated
<b>UN proper shipping name</b>	Not regulated
<b>UN transport hazard class(es)</b>	None
<b>Packing group</b>	None
<b>Environmental hazards</b>	None
<b>Special precautions for user</b>	None

### International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

<b>UN number</b>	Not regulated
<b>UN proper shipping name</b>	Not regulated
<b>UN transport hazard class(es)</b>	None
<b>Packing group</b>	None
<b>Environmental hazards</b>	None
<b>Special precautions for user</b>	None

## SECTION 15: Regulatory information

### United States regulations

**Inventory listing (TSCA):** All ingredients are listed or exempt.

**Significant New Use Rule (TSCA Section 5):** None of the ingredients are listed.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.21.2020

Page 13 of 15

**Dyna Span®, Dyna Slide®, Dyna Shield®**

**Export notification under TSCA Section 12(b):** None of the ingredients are listed.

**SARA Section 302 extremely hazardous substances:** None of the ingredients are listed.

**SARA Section 313 toxic chemicals:**

N/A	Wood/Wood Dust	Not Listed
9003-35-4	*Cured Phenol-Formaldehyde Resin Solids	Not Listed
9016-87-9	*Cured Polymeric Diphenylmethane Diisocyanate (PMDI) Adhesive	Listed
N/A	Polyurea/Polyurethane Solids	Not Listed
68514-74-9	Palm Wax	Not Listed
8030-12-4	Tallow Wax	Not Listed
N/A	Release Agent	Not Listed
N/A	Edge Sealant	Not Listed

**CERCLA:** None of the ingredients are listed.

**RCRA:** None of the ingredients are listed.

**Section 112(r) of the Clean Air Act (CAA):** None of the ingredients are listed.

**Massachusetts Right to Know:**

N/A	Wood/Wood Dust	Not Listed
9003-35-4	*Cured Phenol-Formaldehyde Resin Solids	Not Listed
9016-87-9	*Cured Polymeric Diphenylmethane Diisocyanate (PMDI) Adhesive	Not Listed
N/A	Polyurea/Polyurethane Solids	Not Listed
68514-74-9	Palm Wax	Not Listed
8030-12-4	Tallow Wax	Not Listed
N/A	Release Agent	Not Listed
N/A	Edge Sealant	Not Listed

**New Jersey Right to Know:**

N/A	Wood/Wood Dust	Listed
9003-35-4	*Cured Phenol-Formaldehyde Resin Solids	Listed
9016-87-9	*Cured Polymeric Diphenylmethane Diisocyanate (PMDI) Adhesive	Listed
N/A	Polyurea/Polyurethane Solids	Not Listed
68514-74-9	Palm Wax	Not Listed

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.21.2020

Page 14 of 15

**Dyna Span®, Dyna Slide®, Dyna Shield®**

8030-12-4	Tallow Wax	Not Listed
N/A	Release Agent	Not Listed
N/A	Edge Sealant	Not Listed

### New York Right to Know:

N/A	Wood/Wood Dust	Not Listed
9003-35-4	*Cured Phenol-Formaldehyde Resin Solids	Not Listed
9016-87-9	*Cured Polymeric Diphenylmethane Diisocyanate (PMDI) Adhesive	Not Listed
N/A	Polyurea/Polyurethane Solids	Not Listed
68514-74-9	Palm Wax	Not Listed
8030-12-4	Tallow Wax	Not Listed
N/A	Release Agent	Not Listed
N/A	Edge Sealant	Not Listed

### Pennsylvania Right to Know:

N/A	Wood/Wood Dust	Listed
9003-35-4	*Cured Phenol-Formaldehyde Resin Solids	Listed
9016-87-9	*Cured Polymeric Diphenylmethane Diisocyanate (PMDI) Adhesive	Not Listed
N/A	Polyurea/Polyurethane Solids	Not Listed
68514-74-9	Palm Wax	Not Listed
8030-12-4	Tallow Wax	Not Listed
N/A	Release Agent	Not Listed
N/A	Edge Sealant	Not Listed

### California Proposition 65:

**⚠️ WARNING:** Drilling; sawing, sanding or machining wood products can expose you to wood dust; a substance known to the State of California to cause cancer. Avoid inhaling wood dust or use a dust mask or other safeguards for personal protection. For more information go to [www.P65Warnings.ca.gov/wood](http://www.P65Warnings.ca.gov/wood).

**⚠️ WARNING:** This product can expose you to Formaldehyde; which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## SECTION 16: Other information

**Abbreviations and Acronyms:** None

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.21.2020

Page 15 of 15

**Dyna Span®, Dyna Slide®, Dyna Shield®**

### Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

**NFPA:** 1-1-0

**HMIS:** 1-1-0-E

**Initial preparation date:** 07.21.2020

### Revision Notes:

Revision Date	Notes
2020-07-21	Revision 2: Update to formulation and hazard classification.

**End of Safety Data Sheet**